



KULAK

Where form meets function, the Kulak collection delivers a sophisticated solution for contemporary surfaces. Crafted from multifaced, rectified glazed porcelain, these wall and floor tiles offer seamless transitions between indoor and outdoor spaces.





Available Sizes & Finishes:

In/Out Surface: 30x30, 30x60, 60x60, 60x120

External 60x60 20mm

External 40x60 20mm pencil-edged Bullnose

Colour Range:

Clay – warm and earthy

Sand – soft and neutral

Pearl – luminous and refined

Smoke – cool and modern

Featuring:

Varying faces to give any room a contrasting

& tasteful look any space.

Packing Information

Tile description		Quantity per Box		
Size (cm)	Texture	Pieces	Sqm	Weight (kgs)
30x30	In/Out Surface	11	0.99	19.80
30x60	In/Out Surface	8	1.44	28.20
60x60	In/Out Surface	4	1.44	32.00
60x120	In/Out Surface	2	1.44	37.00
60x60 20mm	External	2	0.72	33.90
40x60 20mm Bullnose	External	3	-	33.80



60x60 Varying faces



60x120 Varying faces

Kulak Smoke



60x60 Varying faces



60x120 Varying faces

Kulak Pearl





60x60 Varying faces



60x120 Varying faces



Kulak Clay



60x60 Varying faces



60x120 Varying faces

Kulak Sand





Kulak Smoke

Technical Specifications: Kulak InOut

	Properties	Test Method	Required Value	Value
	Water absorption	MS ISO 10545-3:2001	$E_6 \leq 0.5\%$ Individual Maximum 0.6%	0.17% 0.16% ~0.19%
	Determination of dimensions	Length and Width	$N \geq 15\text{cm} \pm 0.6\%$ $\pm 2.0\text{mm}$	$0 \sim +0.01\%$ $0 \sim +0.1\text{mm}$
		Thickness	$N \geq 15\text{cm} \pm 5\%$ $\pm 0.5\text{mm}$	$+0.4\% \sim 1.7\%$ $0 \sim +0.2\text{mm}$
		Straightness of Sides	$N \geq 15\text{cm} \pm 0.5\%$ $\pm 1.5\text{mm}$	$-0.01\% \sim +0.01\%$ $-0.1\text{mm} \sim +0.1\text{mm}$
		Rectangularity	$N \geq 15\text{cm} \pm 0.5\%$ $\pm 2.00\text{mm}$	$-0.06\% \sim +0.08\%$ $-0.4\text{mm} \sim +0.5\text{mm}$
	Breakage strength	MS ISO 10545-4:2003	≥ 1300	1899
	Modulus of rupture	MS ISO 10545-4:2003	Minimum 35	39.3
			Individual Minimum 32	37.2 ~41.1
	Chemical resistance	Resistance to household chemicals and swimming pool salts a) Household Chemicals: Ammonium Chloride, 100g/L b) Swimming pool salts: Sodium Hypochlorite solution, 20mg/L Resistance to low concentrations of acids and alkalis a) Hydrochloric acid solutions, 3% (v/v) b) Citric acid solution, 100mg/L c) Potassium hydroxide, 30g/L Resistance to high concentrations of acids and alkalis a) Hydrochloric acid solution, 18% (v/v) b) Lactic acid, 5% (v/v) c) Potassium hydroxide, 100g/L MS ISO 10545-13:2018	Minimum GB Manufacturer to state Classification Test Method available	A LA HA
	Stain resistance	MS ISO 10545-14:2018	Minimum Class 3	Class 5
	Origin	MADE IN CHINA		

Please note that this technical specification sheet is issued to you on an INDICATION ONLY basis as information is subject to shade/production variations, not necessarily to material you would be receiving.
No responsibility will be held for the item not meeting this result.
It is the responsibility of the end user to carry out appropriate testing for the tiles intended use.

Kulak Pearl/60-20MM

60x60 Multiface (24) External 20mm
Rectified Glazed Porcelain

Kulak Pearl/BN-20MM

40x60 Multiface (24) External 20mm
Pencil Edge Bullnose Rectified Glazed
Porcelain





Kulak Clay/60-20MM

60x60 Multiface (24) External
20mm Rectified Glazed Porcelain

Kulak Clay/BN-20MM

40x60 Multiface (24) External
20mm Pencil Edge Bullnose
Rectified Glazed Porcelain